



AltRider Crash Bars for Ducati Multistrada 1200 2015-newer INSTALLATION INSTRUCTIONS

The most up to date instructions can be downloaded from the product page at altrider.com, under the instructions tab.

Dear Rider,
Thank you for choosing AltRider! Whether a seasoned world adventurer or a first time ADV-Newbie, we welcome you to the AltRider experience. You can install your new product with the utmost confidence. AltRider designs, tests, and manufactures all of its products here in the United States. We are proud to do what we do, and honored to present to you the product of our labors.

Enjoy it, show it off, and most of all, RIDE IT!

Venture On,
Jeremy LeBreton



Package Contents:
- left and right crash bars
- mounting brackets
- Hardware kit


AltRider LLC

Global
mailing: 4880 Aurora Ave N Ste 100
Seattle, WA 98103 USA
phone: 206-922-3618
email: info@altrider.com
web: www.altrider.com

Europe
mailing: Oude Nibbelweg 231-M
2691 AG DEN HAAG
Netherlands
email: info@altrider.eu
web: www.altrider.eu

Rare 5
MADE IN THE USA





If you purchased AltRider Frame Sliders with your Crash Bars, then you will not have the (1) M12 x 545 through-bolt.

Kit:

- ① L and R crash bars
- ② (2) M10x25 hex head fasteners
- ③ (2) M6 x25 hex head fasteners
- ④ (2) M8 x15 socket head cap fasteners
- ⑤ L and R brackets
- ⑥ center connector
- ⑦ (1) section of rubber tubing
- ⑧ (2) 8" x 3/16", black double-lock zip-ties
- ⑨ (1) M12 x 347 through-bolt
- ⑩ (2) M12 lock nuts
- ⑪ paper instructions
- ⑫ (2) M8 washers
- ⑬ (2) M12 Washers

Recommended tools:

- ① L and R hardware trays
- ② 3mm, 4mm, 6mm and 8mm allen tools
- ③ 1/4" driver
- ④ 1/2" and 3/8" ratchets
- ⑤ (2) 18mm sockets with short extensions
- ⑥ 1/4" ratchet
- ⑦ 24mm wrench (spanner preferred)
- ⑧ 17mm, 15mm and 13mm sockets
- ⑨ 10mm socket w/short extension
- ⑩ (1) .5ml of thread locker





- ① Take the rubber tube provided and use scissors to split it. Wrap it around the stainless oil line and zip-tie it in place as shown above. (AltRider bracket shown in pic above, but easier to install the rubber tube now before bracket in place)




- ② Oil lines are located above front left corner of radiator.



- ③ (Shown with fairings removed for clarity) Using a 10mm socket and driver, remove the left side upper radiator mount bolt. Attach the bracket in place as shown and use (1) M6 x25 fastener with loctite to mount the bracket (note bracket bends away from bike centerline toward edge of radiator). Install right side bracket in same manner. Leave bolts finger tight. TIP: unclip the oil cooler line.



- ④ Using an 8mm allen key on one side and a 15mm socket on the other, remove the motor mount through bolt.




If you purchased AltRider Frame Sliders with your Crash Bars, please refer to the Frame Sliders instructions document for instructions on assembling this step. DO NOT TIGHTEN TO TORQUE SPEC YET.


- ⑤ Insert one M12 washer into the frame socket. Insert the left side bar into the frame socket. Insert the AltRider engine through bolt.



- ⑥ Insert one M12 washer into the frame socket. Insert the right side bar into the frame socket. Insert the M12 lock nut and use both 18mm sockets (one on each end of engine through bolt) to install nut until just snug, but so bar can still rotate a bit.



- ⑦ Install M10 x 25 hex cap bolts. Use a drop of loctite on each bolt, install finger tight.
- ⑧ Using a 6mm allen tool, attach the center connector bar to the two brackets. Use (2) M8 x 15 socket head cap fasteners with washers, with a drop of loctite on each bolt. Tighten to 10Nm.
- ⑨ Use 15mm socket and tighten both M10 x 25 hex cap bolts to 30 Nm.
- ⑩ Use 10mm socket or open end wrench and tighten both upper radiator mount bolts to 7Nm.





- ⑪ Use both 18mm sockets to tightern both engine bolt lock nuts to 60Nm.



If you purchased AltRider Frame Sliders with your Crash Bars, please refer to the Frame Sliders instructions document for instructions for last steps.

CONGRATULATIONS!

You've completed your installation. If at any point you have questions about your installation or have any feed back for us, we'd love to hear it. A downloadable version of these instructions can be found at our web site. www.AltRider.com

After 5 hours of riding, or 100 miles, check all the fasteners on the assembly to ensure they are tightened to spec.

Global Office:

**email: info@AltRider.com
phone: +1 206-922-3618
address: 4000 Aurora Ave N
Ste 100
Seattle, WA 98103**

Europe Office:

**email: info@AltRider.eu
address: Oude Middenweg 231-M
2491 AG DEN HAAG
Netherlands**

TERMS OF USE, WARRANTY AND LIABILITY WAIVER

AltRider LLC, a Washington company, having its principal place of business in Seattle, WA ("AltRider") offers its motorcycle accessories (the "Product") with the terms, conditions and notices as follows:

Terms of Use

This Product is offered to you conditioned upon your acceptance without modification of the terms, conditions, and notices contained herein. Installation and/or use of this product implies acceptance of all such terms, conditions, and notices. If you do not agree to these terms, do not buy the Product. If you have already bought the Product and do not agree to these terms, return this Product promptly including the packaging and all written materials, to AltRider.

Limitation of Liability and Warranty Disclaimer

You may return your merchandise for a full refund or exchange, less any original or return shipping fees under these conditions:

1. Only if the merchandise is in 100% factory condition. Original manufacturer's packaging and same condition as sold – original boxes, packaging material, instructions, documentation, parts, and attached tags.

2. Only unused, unscratched, uninstalled, undamaged merchandise will be accepted. Do not install equipment until you are sure you want to keep it. Package items carefully in protective materials before returning them. Never ship an item in its original manufacturers packaging – it will arrive damaged. Please use a postal box or other adequate packaging to ensure your return or exchange is not damaged on the way back to AltRider.com.

To read more about our exchanges and returns policy, on the web, navigate to <http://www.altrider.com/info/exchangesAndReturns>

Excepting the warranties stated in the preceding paragraph, AltRider hereby disclaims all other warranties and conditions with regard to the Product including all implied warranties and conditions of merchantability and fitness for a particular purpose. There are no warranties which extend beyond the description on the face hereof. AltRider does not warrant against damages or defects arising out of use or installation of the Product. Installation instructions are provided for your convenience. AltRider is not responsible for any damages arising out of the installation, improper or otherwise, of the Product. No warranty of any kind, expressed or implied, is made regarding the safety of this Product.

To the extent allowed by law, AltRider shall not be held liable for any direct, indirect, punitive, incidental, special or consequential damages arising out of, or connected with, the use or misuse of this Product. Buyer assumes all risks and liability arising from use of this Product.

Entire Agreement

This document states the entire obligation of AltRider with respect to the Product. If any part of this agreement is determined to be void, invalid, unenforceable or illegal, including, but not limited to the warranty disclaimers and liability limitations set forth above, then the remainder of the agreement shall remain in full force and effect.

Applicable Law

This agreement is governed by the laws of Washington, USA. You hereby consent to the exclusive jurisdiction and venue of the courts of Washington, USA, in all disputes arising out of or relating to the use of this product.

