

SLA MAX

READY TO START MAXIMUM POWER

Ready to use, SLA MAX batteries (AGM technology) are **Factory Activated**, completely **spill-proof**, and require **no maintenance**. Specially developed to meet the **superior needs of big-engine bikes** offering **maximum performance**, **maximum reliability** and **extended life**.

ORIGINAL EQUIPMENT
OEM
MANUFACTURER

**plug
and
play**

MAX



FACTORY ACTIVATED

AGM (Absorbent Glass Mat) technology.



READY TO USE

Just plug & play.



NO MAINTENANCE

VRLA (Valve Regulated Lead Acid) design.



SPILL-PROOF DESIGN

Factory sealed & electrolyte held in a glass fiber mat.



NO ACID HANDLING

Very safe.



EXTREME VIBRATION RESISTANCE

Reinforced battery case.



MAXIMUM STARTING POWER & EXTENDED CYCLE LIFE

20% higher than SLA CCA.




SUPERIOR CAPACITY

20% higher than SLA capacity.



MOUNTING ANGLES

HIGH INCLINATION NON-SPILLABLE



COMPATIBLE CHARGERS

BS 10
Battery size up to 20Ah

BS 15
Battery size up to 30Ah

BS 30
Battery size up to 60Ah

BS 60
Battery size up to 120Ah

BK 20
Battery size up to 40Ah

DID YOU KNOW?

SLA MAX range is a perfect solution for ATV, UTV, SSV, watercraft & snowmobile too!

BS BATTERY SLA MAX range is suitable for e-commerce (air freight, road or sea shipment).

FOR HARLEY DAVIDSON - BGZ SERIES

NEW

Developed to fit Harley Davidson bikes, SLA MAX BGZ series offer thus a maximum performance to big engine vehicles with high requirements and with a lot of electronic equipments.

BS BATTERY TYPE	BS CODE	CAPACITY Ah (10Hr)	CAPACITY Ah (20Hr)	CCA A (-18°C)	DIMENSIONS (±2mm)			ASSEMBLY LAYOUT	TERMINAL	REPLACEMENT - MOST POPULAR MODELS	
					L	W	H			SLA / SLA MAX	MF / DRY
BGZ16H	300931	16	16.8	240	150	88.5	145			BTX14H BTX14	BTX14-BS
BGZ16HL	300932	16	16.8	240	150	88.5	145			BTX14HL BTX14L	BTX14L-BS
BGZ20H	300933	20	21.1	320	176	89	157			BTX20H	BTX20-BS
BGZ20HL	300934	20	21.1	320	176	89	157			BTX20HL	BTX20L-BS BTX20HL-BS BB18L-A
BGZ32HL	300935	32	33.7	500	170	132	175			BIX30HL BIX30L	BIX30L-BS BB30L-B



BUILT-IN COPPER NUTS

Enhanced conductivity (up to 50% more than standard terminal) & improved max torque strength (up to 13N.m).



FRONT & TOP CONNECTIONS

Designed to facilitate the mounting on Heavy Duty motorcycles.



TALLER PLATES

For enhanced CCA & Capacity.

FOR BMW

Developed to fit BMW's latest bikes, these SLA MAX models are designed to offer maximal performance with increased capacity and high starting power.

BS BATTERY TYPE	BS CODE	CAPACITY Ah (10Hr)	CAPACITY Ah (20Hr)	CCA A (-18°C)	DIMENSIONS (±2mm)			ASSEMBLY LAYOUT	TERMINAL
					L	W	H		
BTX14H*	300887	14	14.7	220	150	87	145		
BTX16H*	300896	14	16	250	150	87	161		
51913	300860	21	22	275	182	82	171		

FOR POLARIS & INDIAN

Developed to fit Indian's latest bikes, SLA MAX BTX14AH provides increased power, extended life and maximum reliability.

BS BATTERY TYPE	BS CODE	CAPACITY Ah (10Hr)	CAPACITY Ah (20Hr)	CCA A (-18°C)	DIMENSIONS (±2mm)			ASSEMBLY LAYOUT	TERMINAL
					L	W	H		
BTX14AH*	300863	13	13.7	240	134	89	164		

* Models manufactured and designed according to OEM specifications