

PROBEAM®

BY CUSTOM DYNAMICS®

Custom Dynamics®

ProBEAM® Amber 1156

Turn Signals Installation Instructions

We thank you for purchasing the Custom Dynamics® ProBEAM® Amber 1156 LED turn signals! Our LEDs offer maintenance free service and higher visibility. Our ProBEAM® product line utilizes the latest technology and automotive grade components to ensure the highest level of reliable service. Custom Dynamics® offers one of the best warranty programs and customer support in the industry. If you have any questions during the installation of this product please call us at 1(800) 382-1388.

Part Number: PB-A-1156 (Patent Pending)

Package Contents:

- ProBEAM® LED Clusters (1 pair)
- Amber ProBEAM® Lenses (1 pair)

Fitment: Front turn signals on Harley-Davidson® International Models with 1156 single contact bases and Bullet Style (Pop-off) lens.



ATTENTION

Please read all Information below before Installation

Note:

- Use care in removing the OEM lens and bulbs from the housing, so as not to scratch or mar the chrome housing. Custom Dynamics® is not liable for damage to chrome housing during installation.
- Dielectric grease does not need to be used with this LED product, it can actually prevent them from working. Remove any excess grease from your turn signal sockets before inserting.

*****IMPORTANT*****

CAN Bus Models: This LED product is BCM compliant.

However, you must run the 4 way hazard flashers for 3 minutes to allow the BCM to sync the new load after the new LED turn signals are installed.

Non CAN Bus Models: A SMART Signal Stabilizer® or Load Equalizer is required to ensure proper turn signal function and have the proper flash speed.



Installation:

1. Remove the existing lens from turn signal housing.
2. Remove existing bulb from turn signal housing.
3. Remove any corrosion or dielectric grease from the socket to insure the socket contacts are clean.
4. Using a small flat blade screwdriver, go around the perimeter of the reflector and slightly push the black gasket into the housing to allow proper clearance of the new LED turn signal (Refer to Figure 1).



5. Confirm the proper orientation of the socket base and insert the base into the socket. If it seems hard to twist the base in the socket or hard to remove, it is probably orientated the wrong way.

Questions? Call us at: 1 (800) 382-1388 M-TH 8:30AM-5:30PM / FR 9:30AM-5:30PM EST

Installation Instructions - Page 2

Installation Continued:

6. Twist the LED turn signal a few rotations to coil wire from the turn signal to the socket base. Insert LED turn signal into housing and install new lens.
7. Insure the notch in the lens gasket is aligned with the notch in the lens. (Refer to Figure 2.)
9. Check operation of turn signals in all modes.



8. Install the lens on the turn signal housing with the lens notch located at the bottom of the turn signal housing. (Refer to Figure 3.) **Caution:** If there is a gap between the lens and the housing, water will leak into the unit and cause damage, be sure the lens is full seated.



PROBEAM[®]
BY CUSTOM DYNAMICS[®]