

TRIUMPH HEADLIGHT BRACKET

Part No. 09-055

For technical support contact Joker Machine

2245 Kiowa Blvd N. Ste. 100, Lake Havasu City, AZ 86403

PHONE: 909-596-9690, FAX: 909-596-9693

sales@jokermachine.com, www.jokermachine.com

NOTE

Ignition switch must be relocated when installing headlight bracket.

M5 & M6 Allen needed to install Joker Machine Headlight Bracket.

Use medium strength (blue) thread Loctite.

INSTALLATION

1. Use a bike lift to raise the front wheel off the ground. Once that is done you can lower the fork tubes enough to install the Triumph headlight bracket. There's a lot of videos online on how to do this.
2. Loosen upper and lower triple tree pinch bolts. Slide fork tubes down far enough to slide brackets on fork tubes.
3. Before putting the fork tube back together check the headlight bracket fork tube pinch bolts by tightening them down with an M5 allen. All threads are checked at Joker before packaging, but it's better to find out now if there's any thread depth issues that causes the fork tube clamps to not securely tighten around the fork tubes.
4. Put the fork tubes back in place. Refer to the owners manual for pinch bolts torque specs.
5. Place headlight brackets in desired location and tighten pinch bolts using a medium strength (blue) thread Loctite.
6. Install headlight with provided screws and trim washer with M6 allen and medium strength (blue) thread Loctite.
7. If adding turn signals to the headlight bracket use our Headlight Bracket Turn Signal Mounts and install as shown in diagram.

