



● Thank you for Reinforced Chain tensioner KOSO. Before installation, please read the instruction carefully. We recommend that you store the instruction sheet in a safe place for future reference.

⚠ NOTICE

- To install, follow the steps as described in the manual. Any damages caused by not following directions voids warranty.
- Correct tools must be used for installation.
- Do not modify any parts unless specifically stated in the instruction manual.
- Interior controll maintenance should be performed by a professional only.

MARK MEANING:


⚠ Some procedures must be followed to avoid damages to the instrument.

⚠ WARNING! Some procedures must be followed to avoid injuries to the user or others.

⚠ CAUTION! Some procedures must be followed to avoid damages to the vehicle.

☒ Denotes the tightening torque value.

1 ACCESSORY



NOTE Please contact your local distributor if the items received are not the same as the one listed above.

2 INSTALLATION INSTRUCTIONS

Please proceed as follows

- 1 STDM8XP1.25XL25 Screw X1
- 2 STD Washer X1
- 3 STD Shaft X1
- 4 Reinforced Chain tensioner (Accessory 1)
- 5 STD M6 X P1.0 X L16 Screw X1
- 6 Lower Gear (Accessory 2)
- 7 STD M14 X P1.5 X L8.5 Screw X1
- 8 Reinforced Plastic Plug (Accessory 3)
- 9 Washer X1 (Accessory 4)
(only apply if the chain tensioner is too tight after fasten.)

