

INSTALLATION INSTRUCTIONS

PRECISION SPARK PLUG WIRE COVER, GLOSS BLACK

6431

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

WARNING

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- | | | | |
|---|-----------------------|---|------------------------------------|
| 1 | Spark Plug Wire Cover | 1 | Hardware Kit, containing: |
| | | 2 | 1/4-20 X 1/2 Socket Head Cap Screw |
| | | 2 | 1/4 Flat Washers |

YOU WILL ALSO NEED:

Socket Wrench Set, Socket Extension Set, Phillips Screw Driver

PICTURES SHOWN ARE OF THE CHROME PARTS. INSTALLATION OF THE BLACK PARTS WILL BE THE SAME.

NOTICE

THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

STEP 1

Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.

TOP

BOTTOM

PIC 1



1/4 FLAT WASHERS

1/4-20 X 1/2" SHCS

STEP 2

Refer to PIC 2. Remove the seat. Carefully disconnect the anchored cable straps, that retain the spark plug cables, fastened to the frame area under the seat area.

Note: Remove saddle shield heat deflectors if applicable. If heat shields are OEM, discard them. The Spark Plug Wire Cover and heat deflectors will not work together.

STEP 3

FOR WATER COOLED MOTORCYCLES ONLY

Refer to PIC 3. Locate provided Spark Plug Wire Cover. Under the seat area, align the cover over the spark plug cables. Adjust the position of the cables so the cover sits over them with out pinching or bending them.

PROCEED TO STEP 5.



PIC 2

CLUTCH
(LEFT) SIDE
VIEW



PIC 3

KURYAKYN.COM

INSTALLATION INSTRUCTIONS

PRECISION SPARK PLUG WIRE COVER, GLOSS BLACK

6431

-CONTINUED-

STEP 4 FOR OIL COOLED MOTORCYCLES ONLY

Refer to PIC 4 and 5. Locate provided Spark Plug Wire Cover. Under the seat area, gently pull the oil hose down and away from the frame. Carefully place the cover behind the oil hose, and align the cover over the spark plug cables. Adjust the position of the cables so the cover sits over them with out pinching or bending them.

PROCEED TO STEP 5.

STEP 5

Refer to PIC 6 and 7. Locate provided two (2) 1/4-20 X 1/2 Socket Head Cap Screws and two (2) 1/4 Flat Washers. Place washers onto screws. From behind the frame, in the area of the battery, align the lower holes of the frame with the cover. Insert the washer and screw assemblies into the aligned holes. Fully tighten the hardware.


Note: Use an extension for the hex bit to insert and fasten the screw. Apply a little bit of bearing grease to the attached hex bit to prevent the screw from falling off the bit end while installing.

STEP 6

Refer to PIC 8. Reinstall the seat.

NOTICE

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.




PIC 4



PIC 5



PIC 6



PIC 7



PIC 8



FINAL



INSTALLATION INSTRUCTIONS

PRECISION SPARK PLUG WIRE COVER, GLOSS BLACK

6431

-CONTINUED-

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials & workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

1. Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
2. The product must be properly installed, maintained & operated under normal conditions.
3. Kuryakyn shall not be liable for any consequential & incidental damages, including labor & paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn & a customer.
4. Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
5. Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'s contained in components of Kuryakyn products will be warranted for defects in materials & workmanship for 3 years from the date of purchase whereas all other components shall be warranted for one (1) year.
6. All warranty claims must be directed to the place of purchase. Merchandise sold through internet auction sites or any other unauthorized reseller shall not carry a Kuryakyn warranty. If unsure, please contact the place of purchase to verify they are an authorized Kuryakyn reseller.

RETURN POLICY

Merchandise determined to be defective may be returned up to one year from the date of purchase. Returns must be processed through original seller. Returned merchandise for any other reason other than warranty claims must be in like new condition & subject to a 20% restocking fee. All returns are subject to inspection for determination of full or partial credit. Any returned part that shows evidence of being used or installed contrary to manufacturer's instructions, &/or subjected to improper handling, packaging or return shipping by the customer, will not be eligible for exchange, refund or warranty consideration. All returned electrical items will be inspected & tested. If electrical item is deemed functional, no credit will be issued & item will be returned. All sales are final on discontinued or closeout merchandise.

©2015 KURYAKYN HOLDINGS, LLC ALL RIGHTS RESERVED

KURYAKYN, KURYAKYN K logo and the marks appearing on this instruction sheet are registered and common law trademarks of Kuryakyn Holdings except noted third-party trademarks. A full listing of trademarks and trademark registrations owned by Kuryakyn Holdings can be found at www.kuryakyn.com/legal-notice.

Emissions Notice: The California Air Resources Board (CARB) does not permit the use of aftermarket emission-related parts(s) that alter the performance of OEM emission-related devices unless CARB has issued an Executive Order, other than on racing vehicles on closed courses. Check your local laws and manufacturer's information.

Listed Manufacturers and product model names are for reference only. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. All specifications are subject to change without notice.

For additional information on third-party product and company names, please consult our Web page at www.kuryakyn.com/legal-notice

KURYAKYN.COM

