



SYNTHETIC GEAR OIL 75W-90

100% SYNTHETIC, ESTER-BASED GEAR OIL

DESCRIPTION:

Full synthetic, ester-based gear oil specifically formulated for use in motorcycles and ATVs. Unique, oxidatively-stable formulation is designed for transmissions without wet-clutches, differentials with or without hypoid gears and shaft-drives. Proprietary shape combines exotic esters with industry leading extreme pressure and anti-wear additives to reduce friction while ensuring ultimate hardware protection. Exceeds the requirements of API GL-5.

FEATURES & BENEFITS:

- Formulated specifically for use in motorcycles and ATVs
- Excellent in BMW® and Harley-Davidson® applications
- Superior protection and oxidative stability at any temperature
- Shear stable, ester-based formula maintains viscosity while reducing friction for smooth shifting
- Surface-active chemistry aggressively attaches to surfaces, keeping them clean and corrosion-free
- Exceeds API GL-5 specifications

APPLICATIONS:

For all motorcycles and ATVs utilizing transmissions without wet-clutches, differentials with or without hypoid gears and shaft-drives recommending 90wt gear oil. Not for use in transmissions with wet-clutches.

TECHNICAL DATA

SPECIFICATION	TEST METHOD	75W-90
APPEARANCE	VISUAL	Amber
VISCOSITY @ 40°C (cSt)	D445	95.1
VISCOSITY @ 100°C (cSt)	D445	15.4
VISCOSITY INDEX	D2270	165
FLASH POINT (°C)	D92	204
POUR POINT (°C)	D97	-60
DENSITY @ 15 °C (g/ml)	D4052	0.872

EXPERIENCE THE DIFFERENCE

Made In The USA