



MOUNTING SUGGESTIONS:

Harley-Davidson® Softail 2000-2015 Tank Bib

Note: This bib is designed to fit Softails 2000 and up with a squared-off half-dash, as pictured.

Installation of Mustang tank bib:

1. Remove the seat from the motorcycle.
2. Using a ½" wrench, loosen the dash acorn nut and remove the lower panel screw.
3. Lift the back of the dash approximately ½" and slide the panel down off the two mounting tabs and out from under the dash.
4. Lift the dash up and slide the bib under the dash. Cover the two top studs with the dash to ensure it will not slide out. Tighten the dash acorn nut securely.
5. Wrap the hook-and-loop flaps around the frame at the base of the tank.
6. The lower screw is not needed, but can be installed if desired.
7. Re-install seat.



Enjoy the custom look of your new Mustang tank bib!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 93155, 93156, 93310, 93311

You are cordially invited to
— Tour the Mustang Factory —

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.