



MOUNTING SUGGESTIONS:

Suzuki C109 2008-2010 Tank Bib

Installation of Mustang tank bib:

1. Remove the seat from the motorcycle and remove the dash mounting bolt with a 5mm Allen wrench.
2. Slide the dash forward and then lift up off the tank.
3. Position the bib so the cutouts are around the tank's mounting bosses.
4. Slide the dash back into the mounts and secure with the Allen bolt.
5. Using a 12mm wrench, remove the bolt at the base of the fuel tank. Insert the bolt through the mounting hole at the base of the bib and re-install.
6. Re-install seat.



Enjoy the custom look of your new Mustang tank bib!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 9:00 - 5:30 Eastern or send an e-mail to questions@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 93207, 93208, 93342, 93343

**You are cordially invited to
— Tour the Mustang Factory —**

See how our craftspeople take pride in transforming raw materials into the world's highest quality, most comfortable handcrafted seats. Please contact Mustang for more information regarding tours of our historic Three Rivers, Massachusetts, facility (only 75 miles west of Boston; 150 miles northeast of New York City). Our two hour tours are by reservation only; we can accommodate groups from 2 to 24. We promise you will ride away with an entirely new awareness of what you put between you and your bike.