

ITW Permatex Canada
35 Brownridge Road, Unit 1
Halton Hills, ON Canada L7G 0C6
Telephone: (800) 924-6994
Urgence: 800-255-3924 (ChemTel)

Canadian Workplace Hazardous Materials Information System Material Safety Data Sheet

I. PRODUCT IDENTIFICATION

Product Name: GUMOUT CHAIN LUBE
Item No: 29221
Product Type: Aerosol lubricant

II. COMPOSITION/INFORMATION ON INGREDIENTS

| Component: | Weight% | LD50/oral/rat | LC50/inhalation/rat | ACGIH; TLV-TWA |
|--|---------|---------------|---------------------|-------------------------------|
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC 64742-52-5 | 15-40 | >5000 mg/kg | >5 mg/L (4H) | |
| DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC 64742-53-6 | 15-40 | >5000 mg/kg | 2.18 mg/L/4h | 5 mg/m ³ TWA ACGIH |
| PETROLEUM GASES, LIQUEFIED, SWEETENED 68476-86-8 | 10-30 | not available | not available | |

III. PHYSICAL DATA

Physical State/Appearance: Brown foamy/Aerosol
Odour & Odour Threshold: Petroleum
Specific Gravity: 0.880-0.930
Evaporation Rate: <1 (Butyl acetate = 1)
Vapour Pressure: Not determined
Vapour Density: Heavier than air
Freezing Point: Not determined
pH: Does not apply
Octanol/Water Coefficient: Not determined
Boiling Point: >38°C (100°F)

IV. FIRE AND EXPLOSIVE DATA

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Hazardous Combustion Products: Oxides of carbon, Aldehydes
Sensitivity to Static Discharge: Aerosol cans are under pressure and may explode in fire.
Conditions of Flammability: FLAMMABLE: Sprayed product will project flame and may flashback on contact of spray with an ignition source. Contents under pressure. Containers may explode if heated. Use equipment or shielding to protect personnel from bursting containers. Keep containers cool. Vapours are heavier than air and may travel or be moved along the ground to an ignition source.
Flash Point/Range: Flame projection >15 cm but <100 cm.
Autoignition Temperature: Not determined
Upper Explosive Limit: Not determined
Lower Explosive Limit: Not determined

V. REACTIVITY DATA

Conditions Causing Chemical Instability: None
Materials to avoid: Strong oxidizers
Conditions of Reactivity: Avoid excessive heat, sparks and open flame.
Hazardous Decomposition Products: Carbon oxides, Aldehydes

VI. HAZARDS IDENTIFICATION

Primary Routes of Exposure: Eye and skin contact, ingestion, inhalation
Existing Conditions Aggravated by Exposure: Individuals with respiratory problems such as emphysema and asthma should avoid inhalation
Toxicity Information: (See Effects of Acute Exposure to Product)

VI. HAZARDS IDENTIFICATION

| | |
|--|--|
| Effects of Acute Exposure: | Excessive exposure may cause headache, nausea, dizziness and in extreme cases, unconsciousness, respiratory depression. Inhaling may cause mild irritation to the nose, throat and respiratory tract. May cause eye and skin irritation. Intentionally concentrating and inhaling the vapor may be harmful or fatal. |
| Effects of Chronic Exposure: | Long term overexposure to solvents have been associated with lung, liver and kidney damage. Reports have associated repeated and prolonged overexposure to solvents with permanent brain damage and nervous system damage. |
| Irritancy of Product: | Irritation of eyes, skin, nose and throat. May cause dermatitis on prolonged contact in sensitive individuals. Inhalation: Dizziness, anesthesia, unconsciousness, difficulty in breathing. |
| Sensitization to Product: | (See Effects of Acute Exposure to Product) |
| Carcinogenicity: | (See Effects of Chronic Exposure to Product) |
| Reproductive Toxicity: | (See Effects of Chronic Exposure to Product) |
| Teratogenicity: | (See Effects of Chronic Exposure to Product) |
| Mutagenicity: | (See Effects of Chronic Exposure to Product) |
| Toxicologically Synergistic Products: | None known |
| WHMIS Hazard Class: | A COMPRESSED GAS, B5 FLAMMABLE AEROSOLS, D2B TOXIC MATERIALS |

VII. PREVENTATIVE MEASURES

| | |
|---|--|
| Personal Protection | |
| Eyes: | Safety glasses. |
| Skin: | Neoprene or nitrile gloves recommended. |
| Ventilation: | General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product. In case of insufficient ventilation, wear an organic vapor respirator |
| Engineering Controls: | In case of insufficient ventilation, wear an organic vapor respirator |
| Spill Procedures: | Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. |
| Protection of Man and Environment: | Follow Canadian and local regulations for disposal. |
| Handling Procedures and Equipment: | Flammable. Store away from heat, sparks and open flame. Store at temperatures below 50°C. Contents under pressure. Do not puncture or incinerate container. Avoid breathing vapours. |
| Special Handling Information: | Keep away from heat, sparks and open flame. Avoid prolonged breathing of vapor. Keep away from eyes. Avoid prolonged contact with skin. Do not smoke while using. Wash hands after use. |

VIII. FIRST AID MEASURES

| | |
|----------------------|--|
| Ingestion: | Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person. |
| Inhalation: | If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.. |
| Skin Contact: | Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention. |
| Eye Contact: | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists. |

IX. SHIPPING INFORMATION

Canadian Transportation of Dangerous Goods

| | |
|------------------------------|----------------------------|
| Proper Shipping Name: | Aerosols, Limited Quantity |
| Hazard Class: | Class 2.1 |
| UN/ID No: | UN 1950 |

IATA (Air)

| | |
|------------------------------|--------------------|
| Proper Shipping Name: | Consumer Commodity |
| Class or Division: | Class 9 |
| UN/ID Number: | ID 8000 |

IMDG (Vessel)

| | |
|------------------------------|----------------------------|
| Proper Shipping Name: | Aerosols, Limited Quantity |
| Hazard Class: | Class 2.1 |
| UN Number: | UN 1950 |

X. PREPARATION INFORMATION

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 4, PHYSICAL HAZARD 0
(HMIS is a registered trademark of the National Paint and Coatings Association)

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 4, REACTIVITY 0
(NFPA is a registered trademark of the National Fire Protection Association)

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety

X. PREPARATION INFORMATION

Company: ITW Permatex Canada. 35 Brownridge Rd. Unit 1, Halton Hills, ON L76 0C6

Telephone No.: 1-800-924-6994

Revision Date: March 28, 2014

Revision Number: 6