



## ATV REPLACEMENT MUFFLER INSTALLATION INSTRUCTIONS

Visit **QuadBossProducts** on YouTube  
to find installation videos and more.



### 1. Cool Your Engine

Allow the engine cool down long enough for the exhaust to be cool to the touch.

### 2. Remove Surrounding Components

Remove seat, plastics and/or any other items that may be blocking the path to removing your muffler. (Application's may vary) Refer to your vehicle's service manual.

### 3. Cut

"Measure twice, cut once" Not all applications will require the muffler to be cut off. Cut only if your exhaust does not have a coupler in between the muffler and head pipe to separate the two pieces. Measure the overall length of the new QuadBoss Replacement Muffler, cut at the appropriate length to slide into place.

### 4. Loosen

Begin to loosen and remove all hardware that holds the muffler in place.  
Retain all hardware for installation

### 5. Twist

To remove the muffler from head pipe, twist and pull until the muffler slides off the head pipe.

### 6. Sand Paper

Use sand paper to remove any and all residue from the OEM gasket that may be fitted on the end of the head pipe.

### 7. Install

Slide your new QuadBoss Replacement Muffler into the location of the original muffler. Twisting may be needed in order to get the new muffler set in place.

### 8. Retained Hardware

Using the retained hardware, reinstall all hardware in the factory location(s).  
Note: The clamp used to hold the muffler to the head pipe will not be used with the QuadBoss Replacement Muffler.

### 9. Button Up

Reinstall all removed components in reverse order.