# RUGGED FINGER-GRIP HOLDER ASSEMBLY INSTRUCTIONS

SHORT FINGER


Max Depth: 0.75'

Min Width: 1.25"


Max Width: 3.0"

#### PARTS INDEX

- A. BACK PLATE FOR HOLDER (QTY 1)
- B. TOP AND BOTTOM SUPPORTS (QTY 2) (CAN BE REMOVED FOR LARGER DEVICES)
- C. 3 LENGTHS OF FINGER GRIPS (QTY 4 EACH)
- D. VINYL END CAPS (QTY 4)
- E. #8-32 STST NYLOČK NUŤ THIN (QTY 8)
- F. #8-32 X 3/8" MACHINE SCREW (QTY 6)
- G. #8-32 X 5/8" MACHINE SCREW (QTY 2)
- H. #8-32 X 3/4" MACHINE SCREW (QTY 2)









MEDIUM FINGER

Max Depth: 1.25

Min Width: 1.5"

Max Width: 3.5"



LONG FINGER

Max Depth: 1.6"

Min Width: 2.25"

Max Width: 3.5"



- 2. ATTACH (B) SUPPORTS TO TOP AND BOTTOM OF (A) BACK PLATE USING (F) SCREWS AND (E) NUTS. DO NOT TIGHTEN SCREWS YET.
- 3. ATTACH FINGER GRIPS USING (F) SCREWS AND (E) NUTS. DO NOT TIGHTEN SCREWS YET.
- 4. ATTACH (D) VINYL CAPS TO FINGER GRIPS. CUT ENDS IF NEEDED.
- 5. PLACE DEVICE IN HOLDER AND SLIDE FINGER GRIPS AGAINST DEVICE UNTIL FIRM.
- 6. REMOVE DEVICE. TIGHTEN ALL SCREWS WHERE APPROPRIATE.

USE (G) OR (H) SCREWS AND 2 (E) NUTS TO SECURE HOLDER TO YOUR RAM MOUNT

National Products, Inc. 8410 Dallas Ave S. Seattle, WA 98108, (206)-763-8361 www.ram-mount.com

### MOUNTS MADE IN USA Your Best Connection

RMR-INS-UN4

# RUGGED FINGER-GRIP HOLDER ASSEMBLY INSTRUCTIONS

SHORT FINGER


Max Depth: 0.75"

Min Width: 1.25"


Max Width: 3.0"

### **PARTS INDEX**

- A. BACK PLATE FOR HOLDER (QTY 1)
- B. TOP AND BOTTOM SUPPORTS (QTY 2) (CAN BE REMOVED FOR LARGER DEVICES)
- C. 3 LENGTHS OF FINGER GRIPS (QTY 4 EACH)
- D. VINYL END CAPS (QTY 4)
- E. #8-32 STST NYLOCK NUT THIN (QTY 8)
- F. #8-32 X 3/8" MACHINE SCREW (QTY 6)
- G. #8-32 X 5/8" MACHINE SCREW (QTY 2)
- H. #8-32 X 3/4" MACHINE SCREW (QTY 2)









MEDIUM FINGER

Max Depth: 1.25

Min Width: 1.5"

Max Width: 3.5"



LONG FINGER

Max Depth: 1.6"

Min Width: 2.25"

Max Width: 3.5"

- 1. SELECT APPROPRIATE FINGER GRIPS BASED ON DIMENSIONS OF YOUR DEVICE.
- 2. ATTACH (B) SUPPORTS TO TOP AND BOTTOM OF (A) BACK PLATE USING (F) SCREWS AND (E) NUTS. DO NOT TIGHTEN SCREWS YET.
- 3. ATTACH FINGER GRIPS USING (F) SCREWS AND (E) NUTS. DO NOT TIGHTEN SCREWS YET.
- 4. ATTACH (D) VINYL CAPS TO FINGER GRIPS. CUT ENDS IF NEEDED.
- 5. PLACE DEVICE IN HOLDER AND SLIDE FINGER GRIPS AGAINST DEVICE UNTIL FIRM.
- 6. REMOVE DEVICE. TIGHTEN ALL SCREWS WHERE APPROPRIATE.

USE (G) OR (H) SCREWS AND 2 (E) NUTS TO SECURE HOLDER TO YOUR RAM MOUNT



RMR-INS-UN4