

USER GUIDE & INSTALLATION INSTRUCTIONS

DESCRIPTION: GS Heated Seat

PART NUMBER AII

IMPORTANT:

Please read these instructions completely before starting installation. All “**NOTE**,” “**CAUTION**” and “**WARNING**” notations are serious safety issues and should be read carefully. Possible injury to riders or damage to the motorcycle and/or accessory may result if improperly installed.

NOTICE TO DEALERS:

These instructions contain important information for future reference and should be given to the customer.

⚠ WARNING:

READ THESE INSTRUCTIONS THOROUGHLY BEFORE INSTALLATION!

Because of the variety of motorcycle configurations, other accessories, and the features and intended use of this Saddlemen accessory, there are many different mounting options. You are responsible for the proper installation of this accessory on your motorcycle. Your attention to these installation instructions and recommendations will permit safe and proper use of this accessory. You must mount this accessory properly and securely before riding your motorcycle. If you lack the ability to safely and properly install this accessory, seek out a qualified motorcycle technician for assistance. During installation, support the motorcycle with a suitable stand or lift so it will not tip over and injure you, or damage the vehicle. Using or mounting this accessory improperly could result in a loss of control of the motorcycle which could result in damage to your motorcycle or other personal property, the property of third parties, and/or personal injury to yourself or others, up to and including death.

BE SURE TO THOROUGHLY READ AND CLOSELY FOLLOW THE MOUNTING INSTRUCTIONS THAT ARE INCLUDED WITH THIS ACCESSORY:

- Be sure to thoroughly read and closely follow the Mounting Instructions that are included with this accessory.
- For your safety, mount the accessory securely so it will not shift or move while riding. Make sure the accessory will not contact the controls or any other moving parts of your vehicle.
- If this accessory is ever damaged, do not use it until inspected by a professional motorcycle dealer. Replace immediately if it has damage that will prevent it from being properly secured to your vehicle or if it will not securely function as intended.
- If you do not understand the mounting instructions or this warning label DO NOT mount this accessory. Contact your local professional motorcycle dealer for assistance, or call the Saddlemen support line at (310) 638-1222.

DO NOT ATTEMPT TO USE THIS ACCESSORY IF:

- You do not understand these installation and use instructions,
 - You do not understand any part of the accessory mounting system,
- If you have any concerns or questions, seek help at your qualified motorcycle dealer or call the Saddlemen support line at (310) 638-1222.

Remember: Motorcycling can be a dangerous activity. Installation of any accessory can increase your risk if it is not installed properly. You are responsible to install this accessory so it will not contact any portion of the drive train, suspension or steering, or if it will in any way interfere with the operation of your motorcycle.

⚠ WARNING:

To avoid injury, install while engine is cold.

The battery terminals should be disconnected in advance, before working on the motorcycles electrical circuit. When appropriate, the security codes (radio, navigation system, etc.) should be noted.

CAUTION:

Seats with heaters must not be installed in vehicles that will be used by Riders who cannot sense heat or circulation and or a sensory compromised person. There is a High Risk of Thermal Burns.

OVERVIEW:

Thank you for purchasing a Saddlemen Deluxe Motorcycle Touring Saddle; we believe it to be the best seat available for you and your motorcycle. Each was designed for touring riders and high mileage days in the saddle. We make the best seat we can, using only top grade materials and carefully refined contours to provide the most comfortable ride possible.

Optional BUILT-IN / REMOVABLE LUMBAR REST - ADJUSTMENT AND OPERATION

Inside the curved upper rear portion of the pillion seat is a fixed, vertical metal sleeve. Access is through a slot (covered by Velcro) on the top of the rear portion. The sleeve is for containing the bar of the lumbar rest. Install and adjust the lumbar rest as follows:

1. **INSTALLATION** - Grasp the lumbar rest pad and slide it into the hidden metal sleeve. If lumbar rest is "floppy" after installation, it is not inside the sleeve. Remove and reinstall by carefully inserting it into the sleeve.
3. **REMOVAL** - Grasp the lumbar rest. Pull it up and away from the seat.
4. **HEIGHT** - the height of the backrest is adjustable to two positions. Position is determined by detents on the backrest-bar. Adjust height by firmly grasping the pad and lower or raise it to the desired position.
5. **ANGLE** - The backrest-pad is designed to automatically conform to the angle of the driver's back during riding. No adjustment is necessary

INSTALLATION:

Your new GS seat removes and installs identically to the original equipment seat and retails both the high/low adjustability for the driver and fore and aft adjustability for the pillion. For seat removal and installation refer to your motorcycle's owner's manual.

IMPORTANT:

Seat Heater Wiring Instructions

For each wire harness cluster you will have a 4 pin plug which will provide power to the switch and a 3 pin plug which will provide power to the element. When connecting the harnesses to the seat, pay close attention that you mate them correctly.

You are provided with 1 wiring harnesses that you will wire to the motorcycles electrical system. On each harness you will have two wires which are pre-stripped - one Ground (black) and one Positive (red). Connect the Positive wire to the power source on your motorcycle. This can be directly to your battery's Positive (+) terminal, or spliced into a wire or connection that is powered only when the motorcycle's ignition is turned on. Most motorcycles' owner's manuals have a wiring chart to refer to. Connect the Ground wire to your battery's Negative (-) terminal. Make sure that all connections are protected from shorting, and that any extra wire length is neatly wrapped and does not interfere with the seat installation to the motorcycle. If you have any doubts as to your abilities to install this seat and heating element, please see your authorized motorcycle mechanic for installation.

Reinstall the Seat.

BREAK-IN AND MAINTENANCE

Allow a brief break-in period for the Saddlemen seat to conform to your anatomy, and for you to become accustomed to a "new feel". This should be accomplished within your first 500 to 1200 miles. NOTE: Due

to the firmer foam used in a Saddlemen, they will feel higher at first. The Saddlemen will gradually break-in to your anatomy and slightly compress as your mileage increases. It does not breakdown like a factory seat.

SADDLEHYDE CARE -

Saddlehyde™ used in Saddlemen seats needs minimal care. Use commercially available vinyl cleaners or mild soap and water. Additional “conditioners” are not recommended and may cause the vinyl to degrade over time.