

# SPORT USER GUIDE & INSTALLATION INSTRUCTIONS

## SPORT SPORTBIKE SEAT SET



### FEATURES OF THE SADDLEMEN *SPORT* SPORTBIKE SEAT SET:

- Second-to-none styling improves the appearance of your motorcycle and its function.
- Designed specifically for the rider that needs a seat that can do everything — canyon carving, track days, commuting, or 1000-mile days.
- Black-on-black, easy to clean micro-fiber material cover provides cooling, breath-ability and an unmatched look. This unique material covers the entire top portion of the seat with a matching strip in center of the Gel Channel (GC).
- Each *SPORT* seat is slightly bucketed in the rear section to contour to your body for better comfort and control during aggressive riding.
- Features Saddlemen's Gel Channel technology (patent pending) which incorporates gel and a channel in the main foam to relieve pressure on the perineal area and increase blood flow to keep you comfortable and in the saddle longer.
- Matching pillion cover included (so you can match your passenger's seat to the rider's seat).
- Lightweight & Made in the USA.

## ⚠ WARNING

### READ THESE INSTRUCTIONS THOROUGHLY BEFORE INSTALLATION!

Because of the variety of motorcycle configurations, other accessories, and the features and intended use of this Saddlemen accessory seat set, there may be different mounting options. You are responsible for the proper installation of this accessory on your motorcycle. Your attention to these installation instructions and recommendations will permit safe and proper use of this accessory. You must mount this accessory properly and securely before riding your motorcycle. If you lack the ability to safely and properly install this accessory, seek out a qualified motorcycle technician for assistance. During installation, support the motorcycle with a suitable stand or lift so it will not tip over and injure you, or damage the vehicle. Using or mounting this accessory improperly could result in a loss of control of the motorcycle which could result in damage to your motorcycle or other personal property, the property of third parties, and/or personal injury to yourself or others, up to and including death.

### BE SURE TO THOROUGHLY READ AND CLOSELY FOLLOW THE MOUNTING INSTRUCTIONS THAT ARE INCLUDED WITH THIS ACCESSORY:

- The seats must be installed and securely fastened to the motorcycle in the same fashion as the original seats. Refer to your vehicle's Owner's Manual or Service Manual for seat removal and reinstallation instructions.
- If the vehicle's passenger grab strap is removed during the installation of the accessory seat or passenger seat cover make sure it is reinstalled and secure before riding.
- If you do not understand the seat or cover installation instructions DO NOT mount the seat or cover. Remove any items you may have already installed on your motorcycle.
- If your seats are ever damaged, do not use them until they have been inspected by your local professional motorcycle dealer. Replace the seats immediately if they have damage that will prevent them from being properly secured to your motorcycle.

### DO NOT ATTEMPT TO USE THIS ACCESSORY IF:

- You do not understand these installation and use instructions,
- You do not understand any part of the accessory mounting system,
- You have any doubts as to the security of the mounting system.

If you have any concerns or questions, seek help at your qualified motorcycle dealer or call the Saddlemen support line at (310) 638-1222.

Remember: Motorcycling can be a dangerous activity. Installation of any accessory can increase your risk if it is not installed properly. You are responsible to install this accessory so it will not contact any portion of the drive train, suspension or steering, and so that it will in no way interfere with the operation of your motorcycle.

### SPORTBIKE RIDER'S SEAT INSTALLATION INSTRUCTIONS:


Your Saddlemen Sportbike Seat has been developed so it will attach securely to your motorcycle using the same configuration as the vehicle's original seat. Simply refer to your motorcycle's Owner's Manual or Service Manual for the rider's seat removal and reinstallation instructions. Remove the original seat and install your new *SPORT* seat in its place.

**NOTE:** Compare the new seat base to your original seat and transfer any rubber grommets that may be absent. Use soapy water as a lubricant when you remove and install grommets.

### SPORTBIKE PILLION SEAT COVER INSTALLATION INSTRUCTIONS:

Included in your Sportbike Seat Set is a pillion cover you can install on your motorcycle's passenger seat so the texture will match your *SPORT* rider's seat. The new cover ① should be secured in place using an upholstery stapling device. The cover was designed so it could be easily mounted over the original passenger seat cover ②. However the original cover may be removed to achieve a tighter fit for the new cover and to protect the original cover if it is ever desired to return the pillion to its original condition.

**NOTE:** Seat cover installation takes about 30 minutes. Mounting the new seat cover over the existing cover may scuff the original cover's finish. If you wish to preserve the original cover, remove it before installing the new cover. If you lack the tools or the ability to install the cover, seek out a local upholstery shop for assistance. Bring your seats, the new cover and this instruction sheet to the upholstery shop. If you cannot locate someone to perform this service in your community, contact the Saddlemen support line (310-638-1222) as our upholstery technicians can install this cover for you for a \$35.00 fee (plus shipping).



## PILLION SEAT COVER INSTALLATION INSTRUCTIONS (continued):

Refer to your motorcycle's Owner's Manual or Service Manual for the passenger seat removal instructions. Before installing the new *SPORT* seat cover, slip it over the passenger seat and mark the center of the seat on the underside of the new cover, as this will aid you when you align the new cover on the seat base.

Using pliers, carefully pull up and remove at least one seat cover staple from the seat base for study. If you are removing the original seat cover, carefully remove all of the staples and then gently peel the seat cover off, leaving the seat foam in place on the seat base.

**NOTE:** Avoid using a screwdriver or similar tool to pry the staples out so you will not damage the seat base or the cover (in case you choose to remount a removed original cover to the seat in the future). Before installing any new staples, note the length of the removed staple(s). Be sure you are using the same length staples as the one(s) you have removed. This precaution will protect your new seat from potential damage which could occur when using staples that are too long. The incorrect length staple could cause damage to the seat by protruding through the seat base and piercing the seat's foam.

If the new cover is wrinkled, or you desire a very snug fit, warm the cover in the sun or use a hand-held hair-dryer (do not use a heat gun as this can damage the cover). This heat will slightly expand the cover so after it is secured to the seat base and it cools, its surface will be taut and firm.

With the cover ⑤ still warm, slip it on the seat base ⑥, using the mark you made on the inside of the cover to center it on the seat base.




Pull gently on the sides of the cover and staple it into place at four initial points ⑦.

**NOTE:** Insert the staples at the same approximate locations as the original staples. This precaution will protect your new seat cover from damage which could occur if the staples are inserted too close to the seat's edge where they could protrude through the seat base and foam.

Verify that the cover is centered properly and evenly on the seat base, and that its surface is taut and firm. You may then begin to insert other staples using your upholstery stapler ⑧. Pull gently on the cover as you staple it in place so the surface of the cover will be tight. Space the staples approximately 1/2-inch apart around the perimeter of the seat base ⑨. Alternate staple installation from side-to-side and top-to-bottom.

**NOTE:** Work with deliberate care to avoid damaging the cover. As you staple the cover in place, frequently check its appearance on the top of the seat. Do not hesitate to remove staples, adjust the seat cover location or tension, and reinstall the staples. While you want the cover to be taut and firm after installation, take care to not apply too much tension to the cover when you staple it in place. A tear in the cover material is not a defect and is not covered by the Saddlemen Limited Warranty.

If you removed a passenger grab strap from the seat or the chassis when installing the seat or cover, reinstall it when placing the seat on your motorcycle. With the cover installation complete, reinstall the passenger seat per the instructions in your vehicle's Owner's Manual or Service Manual.



## IMPORTANT:

Failure to install the accessory seat, any seat cover, or passenger grab straps properly may allow portions of the seats or related materials to contact the vehicle's moving parts or exhaust system. It is vital that you verify that the seats and any related parts will not touch, or interfere with other components throughout the vehicle's entire range of motion. After 50 miles (80 kilometers) of riding, verify that the seats' mounting is still tight and secure. It is your responsibility to make sure that any accessory installation does not create an unsafe or illegal situation.



### CARE OF YOUR SADDLEMEN ACCESSORY SEATS:

Your Saddlemen seat and seat cover requires almost no maintenance, other than periodic cleaning. Use Saddlemen Seat & Saddlebag Ultra Wash (#3101) for the best results while cleaning, or use mild soap and water.

## SADDLEMEN LIMITED ONE-YEAR WARRANTY

Saddlemen warrants its products for defects in materials, design or workmanship for a period of one year after retail purchase. Items that are defective will be repaired or replaced by Saddlemen at its sole discretion. Damage caused by improper use or improper installation is not a defect; therefore repair or replacement of a damaged accessory will not be covered under this warranty. This warranty contains other provisions and conditions, so please visit [www.saddlemen.com](http://www.saddlemen.com) for additional information. Thank you for purchasing your new Saddlemen accessory. You can count on Saddlemen's quality, innovation, service and style. We want you to be completely satisfied. If you have any comments, or are not satisfied with the performance of your Saddlemen accessory, please contact the Saddlemen support line at (310) 638-1222.



17801 SOUTH SUSANA ROAD, RANCHO DOMINGUEZ, CA 90221 (310) 638-1222 2 / 2

The images in this instruction set may be different than your accessory or motorcycle.

11-0810-SPORT2