ITW Permatex Spray Nine Brands 10 Columbus Blvd. Hartford, CT 06106 USA Telephone: 1-87-Permatex (877) 376-2839 Emergency: 800-255-3924 (ChemTel) International Emergency: +01-813-248-0585 ITW Permatex Canada 35 Brownridge Road, Unit 1 Halton Hills, ON Canada L7G 0C6 Telephone: (800) 924-6994 Urgence: 800-255-3924 (ChemTel)

Material Safety Data Sheet

1. PRODUCT IDENTIFIC	ATION			
Product Name:	Glass & Stainless Stee	el Cleaner		
Product Type:	Aerosol cleaner			
Item Number:	C23319			
2. COMPOSITION/INFOR	RMATION ON INGREDI	ENTS		
Component:	Weight%	ACGIH; TLV-TWA	OSHA PEL	
WATER 7732-18-5	>90	NA	NA	
PETROLEUM GASES, LIQUEFIED, SWEETENED 68476-86-8	1-5	NA	NA	
2-BUTOXYETHANOL 111-76-2	1-5	20 ppm	50 ppm; 240 mg/m ³	
3. HAZARDS IDENTIFIC	ATION			
Effects of Acute Exposure:	May cause eye and skin irritati High concentrations of vapor of	May cause eye and skin irritation High concentrations of vapor or mist may be harmful or irritating if inhaled. Ingestion may cause abdominal pain, vomiting		
Primary Routes of Entry:	Eyes, Skin, Inhalation	Eyes, Skin, Inhalation		
Signs and Symptoms of Exposure	e: Overexposure may cause eye nausea and vomiting.	Overexposure may cause eye and skin redness. Irritating to mucous membranes. Ingestion may cause nausea and vomiting.		
Aggravated Medical Condition:	None known. Preexisting eye, product.	None known. Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.		
Chronic Health Hazard	None known	None known		
4. FIRST AID MEASURE	S			
Eye Contact:	Immediately flush with plenty of	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Contact a physician if irritation persists.		
Skin Contact:	Wash with soap and water. If s launder before reuse.	Wash with soap and water. If skin irritation persists, call a physician. Remove contaminated clothing and launder before reuse.		
Ingestion:		If swallowed, DO NOT induce vomiting. Give victim water, call a physician immediately. Never give anything by mouth to an unconscious person		
Inhalation:	Move to fresh air in case of ac	Move to fresh air in case of accidental inhalation of vapours. If symptoms persist, call a physician.		
Notes to Physician:	Treat symptomatically			
5. FIRE FIGHTING MEAS	SURES			
Flash Point °F(C°):		No flame projection		

Flash Point °F(C°): Recommended Extinguishing Media: Special Fire-Fighting Procedures: No flame projection Carbon dioxide, Dry chemical, Foam Wear suitable protective equipment. Use water spray to cool exposed containers.

5. FIRE FIGHTING MEASURES

Hazardous Products of Combustion: Unusual Fire/Explosion Hazards:

Sensitivity to Static Discharge: Mechanical Sensitivity:

Lower Explosive Limit: Upper Explosive Limit:

6. ACCIDENTAL RELEASE MEASURES

Clean up spills thoroughly as residue is slippery. Prevent from entering waterways or sewers. Contact the proper local authorities.

7. HANDLING AND STORAGE

Keep containers tightly closed in a cool, well-ventilated place. Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C). Keep out of the reach of children. Do not freeze.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Skin: Ventilation: Respiratory Protection: Safety glasses Wear chemical resistant gloves if repeated skin contact occurs or causes irritation. Use only in well ventilated area. Not required under normal use

Oxides of carbon, Oxides of nitrogen

incinerate container.

Not determined

from bursting containers Not determined

Contents under pressure. Heated cans may burst. Do not puncture or

Contents under pressure Use equipment or shielding to protect personnel

Aerosol cans are under pressure and may explode in fire.

9. PHYSICAL AND CHEMICAL PROPERTIES

		•• =••	
Appearance:	Clear liquid	Odor:	Lemon.
Boiling Point:	>200° F/93.3° C	Freezing Point:	~32°F/ ~0°C
pH:	~10.8	Solubility in Water:	Completely soluble
Specific Gravity:	~0.97 g/ml	Vapor Pressure:	Not Determined
Vapor Density (Air=1):	>1	% Volatile:	Not Available
VOC(Wt.%):	<8% by weight	Evaporation Rate:	<1 (Butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability: Hazardous Polymerization: Incompatabilities: Conditions to Avoid: Hazardous Products of Combustion: Stable Will not occur. Strong oxidizers Avoid temperatures greater than 100°F. Freezing conditions. Oxides of carbon, Oxides of nitrogen

11. TOXICOLOGICAL INFORMATION

Product Toxicity Eyes: No data available

Skin: No data available Inhalation LC50: No data available Oral LD50: No data available

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation - DOT - 49 CFR (Ground) DOT Shipping Name: Aerosols, Limited Quantity

Hazard Class: UN/ID Number: Aerosols, Class 2.2 UN 1950

TDG(Transport of Dangerous Goods) Canada

Proper Shipping Name:	Aerosols, Limited Quantity.
Hazard Class:	Class 2.2
UN/ID No:	UN 1950

14. TRANSPORTATION INFORMATION

IATA (Air)

Proper Shipping Name:	Consumer Commodity
Class or Division:	Class 9
UN/ID Number:	ID 8000

IMDG (Vessel)

Proper Shipping Name:	Aerosols, Limited Quantity
Hazard Class:	Class 2.2
UN Number:	UN 1950
Marine Pollutant:	None

15. REGULATORY INFORMATION

SARA 302 Extremely Hazardous Substances:	None
SARA 313 Toxic Chemicals:	2-butoxyethanol (Glycol ethers) Acute health hazard
SARA (311, 312) Hazard Class:	Acute health hazard
TSCA Inventory Status:	All components of this product are listed (or exempt) on the EPA TSCA inventory.
California Proposition 65:	No California Prop 65 chemicals are known to be present.
WHMIS Hazard Class:	A COMPRESSED GAS

16. OTHER INFORMATION

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 4, PHYSICAL HAZARD 0 (HMIS is a registered trademark of the National Paint and Coatings Association)

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 4, REACTIVITY 0 (NFPA is a registered trademark of the National Fire Protection Association)

Prepared By:	Denise Boyd, Manager-Environmental, Health & Safety	Revision Date: February 20, 2015
Company:	ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106	Formula Index: 08
Telephone No.:	1-87-Permatex (877) 376-2839	

DISCLAIMER OF LIABILITY:

The information contained herein is based on data we believe to be reliable as of the date of preparation of the Material Safety Data Sheet. The accuracy and completeness of such data are not warranted or guaranteed. We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products may be used. We assume no liability or responsibility for loss or damage resulting from the improper or abnormal use or handling of our products, from incompatible product combinations, from the failure to follow instructions and warnings in the product's label and Material Safety Data Sheet, or from any failure to adhere to recommended practices.