

MX/OFF-ROAD/ATV/STREET

CHAIN SPECIFICATIONS

QUALITY. DURABILITY. PRICE. SINCE 1946.



Model	Recommended Uses	Length Options	Color Options	Ring Type	Master Link Type	Tensile Strength (lbs)	Weight (lbs per 100 links)	Pin Length (mm)	Max CC Off-Road/Street
HEAVY DUTY									
520HDN	Off-Rd/MX	114 & 120	N	None	Clip	6800	3.15	18.15	250 / NA
520SSR	ATV, Off-Rd/MX, Street	100 & 120	N	O-ring	Clip (PF)	7700	4.08	19.90	400 / 400
520RDG	Street	114 & 120	N	DG	Rivet	8500	3.36	19.90	750 / 750
525RDG	Street	112 & 120	N	DG	Rivet	8850	4.30	22.85	750 / 900
530RDG	Street	110 & 120	N	DG	Rivet	9500	4.48	24.90	750 / 1000
WORKS									
420MXR	Off-Rd/MX	126	G**	None	Clip	5000	1.76	15.70	150 / 150
428MXR	Off-Rd/MX	134	G**	None	Clip	5800	2.13	17.60	150 / 250
520MXRI	Off-Rd/MX	116 & 120	G**	None	Clip	9000	2.99	17.70	500 / NA
520XTG	ATV, Off-Rd/MX	100 & 120	G*	TG	Clip (PF)	8500	3.75	20.80	750 / 400
520RTGI	Street	116 & 120	G**	TG	Rivet	8800	4.30	22.85	750 / 1000
525RTGI	Street	120	G**	TG	Rivet	9300	4.63	22.85	800 / 1100
530RTGI	Street	116 & 120	G**	TG	Rivet	10000	4.63	24.90	900 / 1400

Color: N - Natural | G - Gold / Ring Type: DG - DualGuard (2 sealing lips & lubrication pools per side) | TG - TripleGuard (3 sealing lips & lubrication pools per side) / Master Link Type: PF - Press Fit / (*) Indicates gold outer, non-gold inner plates | (**) Indicates gold outer and inner plates

SUNSTAR MANUFACTURER RECOMMENDATIONS

All chains should be installed by a certified mechanic, using the proper installation tools. Chain adjustment should be done per the bike maker's owner's manual instruction.

Always check sprocket alignment when installing new drive components and during routine maintenance and adjustment; mis-aligned sprockets are detrimental to the life of the drive system.

It is always recommended to replace your chain with the same size (pitch)

and type of chain (sealed or non-sealed) that originally came on the motorcycle from the factory.

Avoid using volatile solvents such as gasoline, thinners and/or benzine; it is best to consult with your local dealer before using any cleaners and/or lubricants.

For best results and the longest life possible replace all drive components (sprockets and chains) at the same time (preferably using both Sunstar chain and sprockets).