



TR-4158S

(2016) YAMAHA YXZ 1000R STAGE 5 SLIP-ON EXHAUST SYSTEM

INSTALLATION INSTRUCTIONS

1. REMOVE THE STOCK SILENCER
2. SLIDE THE T-BOLT CLAMP ONTO THE NEW STAINLESS AND SLIDE IT OVER THE STOCK HEADER
3. INSTALL THE 4-BOLT INLET FLANGE ONTO THE NEW SILENCER WITH THE SPRING TAB ON THE UPPER OUTSIDE BOLT HOLE LOCATION
4. SLIDE THE BILLET MOUNTING BRACKET ONTO THE SILENCER
5. SLIDE THE SILENCER ONTO THE STAINLESS MIDPIPE
6. POSITION THE BILLET CLAMP SO IT MOUNTS TO THE PROPER LOCATION AND INSTALL BOLTS
7. ATTACH THE SPRING FROM THE SILENCER TO THE MIDPIPE
8. ALIGN THE EXHAUST SYSTEM AND SECURE ALL HARDWARE.

WARNING

*Trinity Racing exhaust systems will require adjustment to OEM fuel settings such as jetting changes or installation of an EFI programmer. Trinity Racing will not be held responsible for damages that occur during operation of your vehicle under improper fuel settings. Ultimately, it is the responsibility of the owner/rider to adjust fuel settings to specific riding conditions and elevation changes before riding.

*Inspection of the muffler packing is recommended following every 15 hours of runtime. Failure to maintain muffler packing will result in power loss, increased sound output, and damage to the muffler body or muffler components.

*Trinity Racing exhausts systems are designed for high performance applications and are legal for closed course competition only. This product is not applicable nor intended for use on emissions controlled street, highway, or off-road vehicles.